

Offset paper, natural white, uncoated, matt finish, made from 100% recycled fibre, preprint guarantee

| Basis weight | ISO 536 | g/m ² | 70 | 80 | 90 | 100 | 115 | 135 | 150 | 170 | 190 | 250 | 300 |
|------------------------|------------|--------------------|------|------|------|------|------|------|------|------|------|------|------|
| Thickness / Caliper | ISO 534 | µm | 84 | 96 | 108 | 120 | 138 | 160 | 180 | 204 | 230 | 300 | 360 |
| Specific Volume / Bulk | ISO 534 | cm ³ /g | 1,20 | 1,20 | 1,20 | 1,20 | 1,20 | 1,20 | 1,20 | 1,20 | 1,20 | 1,20 | 1,20 |
| CIE Whiteness | ISO 11475 | % | 90 | 90 | 90 | 90 | 90 | 90 | 90 | 90 | 90 | 90 | 90 |
| ISO Brightness | ISO 2470-1 | % | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 |
| Opacity | ISO 2471 | % | 91 | 93 | 95 | 96 | 97 | 98 | 98 | 98 | 98 | 98 | 98 |
| Moisture (relative) | Tappi 502 | % | 45 | 35 | 35 | 35 | 45 | 45 | 45 | 45 | 45 | 45 | 45 |
| Cobb value 60 sec. | ISO 535 | g/m ² | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 |
| Smoothness (Bendtsen) | ISO 8791-2 | ml/min | 140 | 140 | 140 | 140 | 140 | 140 | 140 | 140 | 180 | 140 | 140 |

All properties are according to mill measurements that may be subject to fluctuations which are customary within the industry.

Applications

- Environmental reports, Flyers, Magazines, Manuals, Newsletters, Brochures, Business documents, Business stationary, Catalogues, Direct mails, Notebooks, Pricelists, Promo cards, Schoolbooks, Children books, Reading books, Writing pads, Tags, Posters

Technical product certificates and information

- Aging resistance (DIN 6738)
- Guaranteed preprint quality

Environmental product certificates and information

- FSC®
- European Ecolabel (EU Flower)
- Nordic Ecolabel (Nordic Swan)
- German Ecolabel (Blue Angel)
- Cradle to Cradle Silver
- Process chlorine free (PCF)



www.blauer-engel.de/uz14a



Supplier certificates

- FSC®
- PEFC™
- Environmental Management System (ISO 14001)
- Quality Management System (ISO 9001)
- Occupational Health and Safety Management System (OHSAS 18001)

Technical capability

| | |
|------------------------|---|
| Printing technologies: | Absorbent substrate that is suitable for offset, UV-offset and screen printing. A sufficient quantity of printing powder with an appropriate particle size has to be considered. |
| Screen ruling: | All conventional screen rulings up to 60 l/cm (150 lpi) are applicable. When using other screen technologies, tests are recommended before print production. |
| Printing inks: | Suitable for inks drying by absorption and oxidation (Offset) and UV-inks. |
| Ink drying: | The drying process of the conventional offset ink is entirely completed within 24 to 48 hours, depending on the thickness of the ink film. |
| Printing pressure: | Standard pressure. Slightly increased pressure on bulky papers and usage of soft rubber blankets is recommended. |
| Finishing: | Varnishing with overprint and water-based varnishes, as well as hot foil stamping, embossing and die-cutting are applicable. A finishing with UV-varnish has to be checked in advance and could require a pre-coating with a primer. |
| Hot foil stamping: | suitable |
| Creasing & folding: | In order to obtain the best possible folding results, the folding process has to be prepared via creasing, while the common standard values for creasing have to be considered. |
| Handling information: | The flatness of this paper is guaranteed at a relative humidity between 45 and 55% at a temperature between 20 and 23°C. It is recommended that the printing room has comparable climatic conditions. The paper should be kept as long as possible in the mill-wrapper before use. Extreme changes in temperature and humidity should be avoided. |

For all printing and processing techniques, the recommendations of the manufacturers of machines, inks, adhesives, laminating and embossing foils, etc. are to be followed. For damages caused by faulty implementation of printing and processing, Papyrus cannot accept any liability.

Can be subject to printing errors and modifications